Commercial Fishing Vessel Safety Exam Checklist Documented Vessels < 40', ≤ 50 miles from shore

Vessel Name:	Number:			
BRIDGE & DOCUMENTS				
33 CFR 173 46 CFR 67	Registration/Documents/Markings: Certificate of documentation on board & valid. Name on both sides, forward part of hull, name & hailing port on stern, ≥ 4" letters, contrasting color. Official number permanently marked on main beam.	O Yes O No O N/A		
46 CFR 28.165	Injury Placard: Required on all vessels.	O Yes O No O N/A		
33 CFR 155.450	Oil Pollution Placard: Required on all vessels $\geq 26^{\circ}$.	O Yes O No O N/A		
33 CFR 151.59	MARPOL (Garbage) Placard: Required on all vessels ≥ 26°.	O Yes O No O N/A		
33 USC 1602 33 USC 2020 72 COLREGS	Navigation Lights: During darkness and/or in or near areas of restricted visibility Side Lights (112.5°), all around white light (if <12m or 39.4') or Mast Head Light (225°) & Stern Light (135°). Fishing Lights: In a vertical line, one meter apart. Red over White (360°) all other than trawling; Green over White (360°) when trawling.	O Yes O No O N/A		
33 USC 1602 33 USC 2020 72 COLREGS	Dayshapes: Two black cones, apex to apex (not required on trollers).	O Yes O No O N/A		
33 USC 1602 33 USC 2020 72 COLREGS	Sound Producing Devices: Vessels < 12m: Some means of making an efficient sound signal. Vessels ≥ 12m: Whistle audible for ½ mile & 7.9" bell.	O Yes O No O N/A		
46 CFR 28.210	First Aid/CPR: Requires first aid & CPR trained & certified persons on board (POB) as follows: > 3 POB, one each; >17 POB, two each; one POB holding both certifications is acceptable. Requires "suitable" first aid kit & first aid manual.	O Yes O No O N/A		
46 CFR 28.225	Navigation Publications: Requires corrected marine charts of operating area, U. S. Coast Pilot, Coast Guard Light List, Tide & Tidal Current Tables & (if > 12m or 39.5') a copy of Inland Navigation Rules.	O Yes O No O N/A		
46 CFR 28.230	Magnetic Compass/Compass Deviation Table: Requires operable magnetic compass at operating station & a current compass deviation table.	O Yes O No O N/A		
46 CFR 28.245 47 CFR 80 33 CFR 26.03 46 CFR 28.375	Communication Equipment: Requires a VHF-FM radiotelephone (156 – 162 MHz) & single side band radio(s) (when 20 - 100 miles, 2 - 4 MHz frequency band) at the operating station, all capable of operating three hours off an emergency power supply.	O Yes O No O N/A		
47 CFR 80.405	FCC Ship Radio Station License: If operating beyond the Boundary Line, all documented vessels required to carry radio transmitting equipment are required to have on board a current FCC Ship Radio Station License.	O Yes O No O N/A		
46 CFR 28.240	General Alarm System: If there is an accommodation or workspace not adjacent to the operating station, requires an audible general alarm system with contact maker at the operating station; flashing red light in workspaces where the audible alarm is hard to hear (engine room), & red-letter warning signs "Attention General Alarm – When Alarm Sounds, Go To Your Station" at each bell or light. Public address system may be used if it meets criteria. Test prior to operating vessel & wooldy of the words.	O Yes O No O N/A		
46 CFR 28.250	weekly afterwards. High Water Alarms: If \geq 36', requires a visible & audible alarm at operating station to indicate high water in normally unmanned or non-watertight spaces (engine room, lazarette, fish hold, etc.).	O Yes O No O N/A		
46 CFR 28.265	Emergency Instructions: Requires written Emergency Instructions. Must be posted if \geq 4 POB, kept available if \leq 4 POB.	O Yes O No O N/A		
46 CFR 28.270	Instructions, Drills, & Safety Orientation: Requires master or individual-in- charge ensure monthly drills & instructions given to each person on board by a trained drill conductor. There are ten Required Drills & Instructions. Before operating vessel, persons on board who have not had drills & instruction must receive a safety orientation.	O Yes O No O N/A		
46 CFR 28.235	Anchors & Radar Reflectors: Requires radar reflector if vessels lacks strong radar signature (usually fiberglass hull vessels). Requires adequate anchor & sufficient line/cable for operating area.	O Yes O No O N/A		

Commercial Fishing Vessel Safety Exam Checklist Documented Vessels < 40', ≤ 50 miles from shore

LIFESAVING				
46 CFR 28.145	Visual Distress Signals: 3 hand-held rocket-propelled parachute red flares plus six	O Ves	O No	O N/A
46 CFR 28.140	hand red flares plus three floating orange smoke distress signals.	0 103	0 110	0 11/11
46 CFR 28.110	Personal Flotation Devices (PFDs): Requires one immersion suit for each person			
46 CFR 28.135	on board. Immersion suit needs PFD light; PFD marked w/name of vessel/wearer	O Yes	O No	O N/A
46 CFR 28.140	& retroreflective tape (31 sq. in.) front & back, properly maintained & stowed	0 100	0 110	0 1 1/11
	readily accessible.			
46 CFR 28.115	Ring Life Buoys: One 24" ring life buoy marked w/vessel name/number, four	O Yes	O No	O N/A
46 CFR 28.135	strips of retroreflective tape, 60' of floating line & stowed readily accessible.			
46 CFR 28.120	Survival Craft: Inflatable liferaft w/Coastal Service equipment pack required for			
46 CFR 28.125	warm water operations, may be stowed to float free or kept readily accessible.	O Voc	O No	O N/A
46 CFR 28.130	Inflatable liferaft w/SOLAS "B" equipment pack required for cold water	0 103	UNU	U IV/A
46 CFR 28.140	operations, must be stowed to float free & automatically inflate.			
ENGINE ROOM/MISCELLANEOUS				
46 CFR 28.155	Portable Fire Extinguishing Equipment: Two B-I or one B-II fire extinguisher			
46 CFR 28.160	on board. Must be USCG, UL or FM approved; mounted in approved bracket; in	O Yes	O No	O N/A
46 CFR 25.30	good condition; must have pressure gauge or inspection record.			
46 CFR 25.35	Flame Arrestor: If using gasoline as fuel only.	O Yes	O No	O N/A
46 CFR 25.40	Ventilation: If using gasoline as fuel only.	O Yes	O No	O N/A
	Marine Sanitation Device: Type I, II or III; required only if there is an installed			
33 CFR 159.7	toilet on board; Type III must be fitted with a positive means (padlock/wire tie) of	O Yes	O No	O N/A
	securing overboard discharge valve when vessel is not > 3 miles from shore.			
	Guards for Exposed Hazards: Requires suitable hand covers, guards, or railings		•	·
46 CFR 28.215	in way of machinery (gearing, chain or belt drives, rotating shafts, etc.) that may	O Yes	O No	O N/A
	injure personnel. Not to restrict access to fishing gear.			
46 CFR 28.255	Bilge Pump, Piping & Dewatering Systems: Requires bilge pumps & piping	O Vec	O Na	O NI/A
40 CFR 28.233	capable of dewatering any watertight space.	U Yes	U NO	O N/A

To schedule a "no fault, no penalty" voluntary dockside examination, please contact one of these fishing vessel safety professionals:

In Maryland, call: In Virginia, call: In southern New Jersey, call: In North Carolina, call the Baltimore, MD Examiner at (410) 576-2634 the Norfolk, VA Examiner at (757) 668-5533 the Philadelphia, PA Examiner at (215) 271-4989 the Atlantic Beach, NC Examiner at (252) 247-4562